

Unit: mm

Designation (Názov)	d	D	Recommended Tolerances (Odporúčané tolerancie)				Thickness (T) (Hrúbka)		Hole Diameter (h) (Priemer poistného otvoru)		Position of the hole (M) (Poloha poistného otvoru)		t	D1
			d		D								+/- 0,2	+ 0,12
B20WC10 KX	10	20	0	0,25	0	-0,25	1,45	1,5	1,625	1,875	14,875	15,125	1,0	20
B20WC12 KX	12	24	0	0,25	0	-0,25	1,45	1,5	1,625	1,875	17,875	18,125	1,0	24
B20WC14 KX	14	26	0	0,25	0	-0,25	1,45	1,5	2,125	2,375	19,875	20,125	1,0	26
B20WC16 KX	16	30	0	0,25	0	-0,25	1,45	1,5	2,125	2,375	22,875	23,125	1,0	30
B20WC18 KX	18	32	0	0,25	0	-0,25	1,45	1,5	2,125	2,375	24,875	25,125	1,0	32
B20WC20 KX	20	36	0	0,25	0	-0,25	1,45	1,5	3,125	3,375	27,875	28,125	1,0	36
B20WC22 KX	22	38	0	0,25	0	-0,25	1,45	1,5	3,125	3,375	29,875	30,125	1,0	38
B20WC24 KX	24	42	0	0,25	0	-0,25	1,45	1,5	3,125	3,375	32,875	33,125	1,0	42
B20WC26 KX	26	44	0	0,25	0	-0,25	1,45	1,5	3,125	3,375	34,875	35,125	1,0	44
B20WC28 KX	28	48	0	0,25	0	-0,25	1,45	1,5	4,125	4,375	37,875	38,125	1,0	48
B20WC32 KX	32	54	0	0,25	0	-0,25	1,45	1,5	4,125	4,375	42,875	43,125	1,0	54
B20WC38 KX	38	62	0	0,25	0	-0,25	1,45	1,5	4,125	4,375	49,875	50,125	1,0	62
B20WC42 KX	42	66	0	0,25	0	-0,25	1,45	1,5	4,125	4,375	53,875	54,125	1,0	66
B20WC48 KX	48	74	0	0,25	0	-0,25	1,95	2,00	4,125	4,375	60,875	61,125	1,5	74
B20WC52 KX	52	78	0	0,25	0	-0,25	1,95	2,00	4,125	4,375	64,875	65,125	1,5	78
B20WC62 KX	62	90	0	0,25	0	-0,25	1,95	2,00	4,125	4,375	75,875	76,125	1,5	90